

NOTE N-630

SEA SURFACE WIND SPEED FROM SPACE

John J. Martin
INSTITUTE FOR DEFENSE ANALYSES
// Arlington, Virginia

September 1969

20100915210

IDA Log No. Hq. 69-10723
Copy **86** of 130 copies

INTERNAL AND RELEASABLE NOTE DISCLAIMER

Distribution of this document
is unlimited.

Any views expressed in this Note are those of the author. They should not be interpreted as reflecting the views of the Institute for Defense Analyses or the official opinion or policy of any of its sponsors.

DTIC® has determined on 10/18/2010 that this Technical Document has the Distribution Statement checked below. The current distribution for this document can be found in the DTIC® Technical Report Database.

☒ **DISTRIBUTION STATEMENT A.** Approved for public release; distribution is unlimited.

☐ **© COPYRIGHTED;** U.S. Government or Federal Rights License. All other rights and uses except those permitted by copyright law are reserved by the copyright owner.

☐ **DISTRIBUTION STATEMENT B.** Distribution authorized to U.S. Government agencies only (fill in reason) (date of determination). Other requests for this document shall be referred to (insert controlling DoD office)

☐ **DISTRIBUTION STATEMENT C.** Distribution authorized to U.S. Government Agencies and their contractors (fill in reason) (date of determination). Other requests for this document shall be referred to (insert controlling DoD office)

☐ **DISTRIBUTION STATEMENT D.** Distribution authorized to the Department of Defense and U.S. DoD contractors only (fill in reason) (date of determination). Other requests shall be referred to (insert controlling DoD office).

☐ **DISTRIBUTION STATEMENT E.** Distribution authorized to DoD Components only (fill in reason) (date of determination). Other requests shall be referred to (insert controlling DoD office).

☐ **DISTRIBUTION STATEMENT F.** Further dissemination only as directed by (inserting controlling DoD office) (date of determination) or higher DoD authority.

Distribution Statement F is also used when a document does not contain a distribution statement and no distribution statement can be determined.

☐ **DISTRIBUTION STATEMENT X.** Distribution authorized to U.S. Government Agencies and private individuals or enterprises eligible to obtain export-controlled technical data in accordance with DoDD 5230.25; (date of determination). DoD Controlling Office is (insert controlling DoD office).

SEA SURFACE WIND SPEED FROM SPACE

J. J. Martin*
Institute for Defense Analyses
Arlington, Virginia

ABSTRACT

The availability of sea surface slope variance and reflectance as a function of wind speed at the sea surface makes possible the measurement of that wind speed from space. This paper treats a simple case, i.e., flat-earth, using vertical viewing and solar flux. Generalization to a spherical earth, oblique viewing and radar as well as optical wavelengths is possible.

FOOTNOTE TO ABSTRACT

*Director, Systems Evaluation Division

Some years ago, Cox and Munk [1954] showed through recourse to photographs of sun's glitter that the variance of sea surface slopes was a linear function of wind speed over the sea surface. In fact, they developed all the methodology for measuring sea surface wind speed from aloft lacking only sea surface radiance over a range of wind speeds to effect the method. Recently Martin [1966] has determined such a relationship.

Simply put, if an optical or radar sensing system views a sea surface glittering spot of electromagnetic waves then, given the local intensity of glitter within the spot as a function of spot off-center angle, one may deduce wind speed. Furthermore, as up-wind and cross-wind clean surface slope variances differ by a factor of as much as 1.5 one might, in principle, deduce wind direction also if wind speeds are large enough.

Rather than immediately complicate matters by involving spherical geometry and radiant source and sensing system in general positions, it is better to describe the idea by using flat earth and a plane vertical to it.

Cox and Munk showed that for both clean sea surface and slick sea surface, for both cross-wind and up-wind directions, slope variance σ_z^2 , may be represented as

$$\sigma_z^2 = a + bv \quad (1)$$

where v is wind speed measured 41 feet above sea level and a and b are constants depending upon sea surface cleanliness and wind direction. The appropriate values are given in Table 1 for v in m/sec.

TABLE 1. Coefficients for Sea Surface Slope Variance
(cf. Eq. 1, Cox & Munk [1954])

Surface Condition	Constant, a		Wind Speed Coefficient, b	
	Up-wind	Cross-wind	Up-wind	Cross-wind
Clean Surface	0.000	0.003	0.00316	0.00192
Slick Surface	0.005	0.003	0.00078	0.00084

The other necessary basis for estimating sea surface wind speed from aloft is the surface reflection strength as a function of wind speed and geometry of interest. Without distinguishing between clean or slick surfaces, Martin [1966, 1968A] gives reflection strength J based on acoustic, radar, laser, and water surface slope spectra data as follows:

$$J = J_0(v) \exp \left[-\frac{1}{2} \left(\frac{\tan \theta}{\sigma_z'} \right)^2 \right] \quad (2)$$

where $J_0(v)$ is the reflection strength of the sea surface along rays from specular points on the surface with local slope $\theta = 0$. As a function of wind speed, $J_0(v)$ expressed in decibels, i.e., $N_0(v) \equiv 10 \log J_0(v)$, is given the form of an error integral, i.e., (Martin [1968A])

$$N_0(v) = (A/\sqrt{2\pi} \sigma) \int_{-\infty}^x \exp \left\{ -\frac{1}{2} [(x' - \mu)/\sigma]^2 \right\} dx' \quad (3)$$

where $x = \ln v$, $A = -10$, $\mu = \ln (4.9 \text{ m/sec})$ and $\sigma = \ln (1.95 \text{ m/sec})$.

Now with the foregoing as basis, assume that the geometry of Fig. 1 is of interest. That is, the sun's rays are illuminating the sea surface at normal incidence and the sensing system is viewing normal to the sea surface also. In Eq. 2, it is apparent--from Fig. 1--that θ , the local slope required for specular reflection, is replaced by ϕ the off-axis viewing angle of the sensing system. Hence, with Eqs. 1, 2, and 3, one may compute reflection strength $N(v, \phi)$ as shown in Fig. 2.

Figure 2 is calculated as if there were no attenuation between the source surface and sensing system, which need not be the case. However, in case transmission of the atmosphere is unity, then a measurement of glitter spot center intensity is a direct measure of sea surface wind velocity. In addition, under such a circumstance the measurement of $N_0(v, \varphi)$, where φ is an arbitrary but fixed value, determines v redundantly, as implied by Fig. 2.

More likely, however, transmission of the atmosphere will be less than unity and unknown and glitter spot center relative intensity as well as $N(v, \varphi)$ will be required to fix v , the sea surface wind speed. To this end suppose, for example, that the sensing system has a "gate" of sensitivity with a 40-db dynamic range, and that by means of attenuators or filters, this dynamic range is "tunable." Thus to determine v_1 the gate would be tuned so as to cause the glitter spot maximum intensity to be at the point of saturation and the spot size threshold level would then determine wind speed. For the threshold shown in Fig. 2, i.e., 40 db, it happens that v varies about as φ^2 .

It seems clear that if one were to trace out the glitter spot in two dimensions on the surface that an oblong spot would develop due to the variance differences indicated in Table 1. For the same 40-db gate postulated above, Fig. 3 shows glitter spot size for various wind speeds. At low wind speeds, the major axis of the ellipse is in the cross-wind direction--or so Table 1 and Eq. 1 indicate--and with increasing wind speed the major axis turns to the windward direction. The properties of conics indicate that the pattern is circular at about 2.5 m/sec and that the asymptotic eccentricity of the elliptical glitter spot at large wind speeds is about 5/8. Because the glitter spot angular extent ϕ varies as $v^{1/2}$ and as the area of the glitter spot varies as ϕ^2 , it appears that in addition to measuring angular extent to estimate wind speed, a raster scan (area integration) of the glitter spot could give a measurement of wind speed also.

A comment on the 40-db threshold of the example is warranted. The technique being used depends upon reflection from "facets" of sea surface rather than upon scattering due to resonance between incident

radiation and Fourier components of the sea surface elevation. Thus, reflection strength must be large enough so that it is not confused with scattering strength. There is some evidence [Martin, 1968A] that for wavenumbers less than about 50/cm (wavelength \cong 1 to 2 mm) that an upper bound on unattenuated scattering strength is -26 db even at the greatest wind speeds. At wavenumbers greater than 50/cm, sea surface elevation spectral density drops off very rapidly [Martin, 1968B] with increasing wavenumber so that a 40-db dynamic range is not unreasonable for optical (IR-UV) wavelengths.

Thus it appears that the combined variation of sea surface reflectance and slope variance is suitable for measuring sea surface wind speed. These wind speed measurements could be made by passive or active, optical, electro-optical or radar systems, and might yield in addition wind direction--with an uncertainty of 180 deg. at large enough wind speed. The 180 deg. uncertainty might be removed by recourse to atmospheric circulation principles or to other data.


REFERENCES


- Cox, C.S. and W.H. Munk, "Measurement of the roughness of the sea surface from photographs of sun glitter," J. Opt. Soc. Am., 44, 838-850, 1954.
- Martin, J. J., "Acoustic reverberation at the sea surface: surface and sublayer spectra vis-a-vis scattering and reflection," Defense Documentation Center AD645 541, 1966.
- Martin, J. J., "Sea surface reflection strength from acoustic, laser, and slope spectra measurements," to be submitted to J. Geophys. Res., 1968A.
- Martin, J. J., "Capillary wave spectra from sound reverberation measurements," submitted to J. Geophys. Res., April 1968B.


FIG. 1. Simple Case Using Vertical Viewing and Solar Flux

FIG. 2. Glitter Spot Reflectance vs Angular Distance

FIG. 3. Glitter Spot Size for Various Wind Speeds







DISTRIBUTION LIST

	<u>No. of Copies</u>		<u>No. of Copies</u>
Commander Antisubmarine Defense Force U.S. Atlantic Fleet Norfolk 11, Virginia	1	Assistant Director of Defense Research and Engineering (Sea Warfare Systems) Pentagon, Room 3D1048 Washington 25, D. C.	2
Commander Antisubmarine Warfare Force U.S. Pacific Fleet Navy No. 128 c/o Fleet Post Office San Francisco, California	1	Director Advanced Research Projects Agency Pentagon, Room 3E160 Washington, D. C.	1
Naval Material Command SPOO-1 Special Projects Office Washington 25, D. C. Attn: Dr. J. P. Craven Code RU-221	2	Technical Information Office Advanced Research Projects Agency Pentagon, Room 2B261 Washington 25, D. C.	1
Director, Naval Material Command Special Projects Office SP-43 Washington 25, D. C.	1	ASD (Systems Analysis) Pentagon, Room 3C860 Washington 25, D. C.	1
Chief, Naval Material Command Department of the Navy Undersea Warfare Office Washington 25, D. C. Attn: Code R-56	1	Director Weapons Systems Evaluation Group 400 Army-Navy Drive Arlington, Virginia	1
Naval Ship Systems Command Department of the Navy Washington 25, D. C. Attn: Code 688 (5 copies) Code 1622	6	Commander Destroyer Development Group II U.S. Atlantic Fleet Newport, Rhode Island	1
Chief, Naval Ship System Command Environmental Effects & Oceanography Washington 25, D. C. Attn: Mr. B. K. Couper	1	Commanding Officer Fleet Sonar School Key West, Florida	1
Director of Defense Research and Engineering Pentagon, Room 3C128 Washington 25, D. C. Attn: Technical Library (1) Mr. Clements (3) Dr. Sebastyan (1)	5	Commanding Officer Fleet Training Center Norfolk, Virginia	1

	<u>No. of Copies</u>		<u>No. of Copies</u>
U.S. Navy Oceanographic Office Suitland, Maryland ATTN: Cdr. John Frey W. H. Geddes	2	Director Ordnance Research Laboratory Pennsylvania State University University Park, Pennsylvania	1
Commanding Officer and Director U.S. Navy Underwater Sound Laboratory Fort Trumbull, New London, Conn. ATTN: Mr. S. A. Peterson	1	Director Applied Physics Laboratory University of Washington Seattle, Washington ATTN: Dr. G. R. Garrison	1
Woods Hole Oceanographic Institution Woods Hole, Massachusetts ATTN: Dr. J. B. Hersey	1	University of Texas Defense Research Laboratory 500 E. 24th Street Austin 12, Texas	5
Scripps Institution of Oceanography University of California LaJolla, California ATTN: Dr. C. Cox Dr. W. Munk	2	ATTN: G. R. Barnard J. L. Bardin C. W. Horton C. M. McKinney S. P. Pitt	
Institute of Marine Science University of Miami Miami, Florida ATTN: J. C. Steinberg	1		
AVCO Marine Electronics Office 33 Union Street New London, Connecticut ATTN: Dr. H. W. Marsh	1	Vice Adm. C. B. Martell Director of Antisubmarine Warfare Programs Office of the Chief of Naval Operations Room 5D569 Pentagon Washington, D. C.	2
Brown University Research Analysis Group 180 Hope Street Providence, Rhode Island	1	Admiralty Research Laboratory Teddington, England ATTN: Mr. D. E. Weston	1
Canadian Joint Staff Defense Research Board Member 2450 Massachusetts Avenue, N.W. Washington, D. C.	1	Defense Documentation Center Building 5 Cameron Station Alexandria, Virginia	20
Columbia University Hudson Laboratories 145 Palisade Street Dobbs Ferry, New York	1		
The Johns Hopkins University Applied Physics Laboratory 8621 Georgia Avenue Silver Spring, Maryland	1		

	<u>No. of Copies</u>		<u>No. of Copies</u>
Institute for Naval Studies 185 Alewife-Brook Parkway Cambridge 28, Massachusetts	1	Commanding Officer and Director U. S. Navy Mine Defense Laboratory Panama City, Florida	1
ATTN: Director		Commander	1
National Research Council Executive Secretary Committee on Undersea Warfare Washington, D.C.	1	U.S. Naval Air Development Center Johnsville, Pennsylvania	
		ATTN: Dr. J. R. Howard	
Office of Naval Research Department of the Navy Washington, D.C.	4	Commanding Officer and Director David Taylor Model Basin Washington, D. C. 20007	1
ATTN: Mr. B. G. Bingham, Code 466 Mr. Morscher, Code 492 Mr. H. A. O'Neal, Code 467		ATTN: Dr. M. Strasberg	
Mr. J. W. Smith, Code 406T		U.S. Naval Ordnance Laboratory White Oak, Maryland	2
		ATTN: Mr. B. L. Snavelly Mr. R. J. Urick	
Director North Atlantic Treaty Organization SACLANT ASW Research Center APO 09019, New York, New York	1	Commander, U.S. Naval Ordnance Test Station China Lake, California	3
Arthur D. Little, Inc. 35 Acorn Park Cambridge 40, Massachusetts	1	ATTN: Code 753 (3 copies)	
Commanding Officer Office of Naval Research Branch Office 495 Summer Street Boston 10, Massachusetts	1	Director U.S. Naval Research Laboratory Washington 25, D. C.	3
ATTN: Dr. F. V. Hunt		ATTN: Mr. Burt Hurdle Mr. A. T. McClinton Mr. R. B. Patterson	
Commander Submarine Development Group II Box 70, USN Submarine Base Groton, Connecticut	1	Commanding Officer U.S. Naval Underwater Ordnance Station Newport, Rhode Island	1
Marine Physical Laboratory Scripps Institution of Oceanography University of California San Diego 52, California	1	Commander U.S. Naval Weapons Laboratory Dahlgren, Virginia	1
U.S. Naval Academy Science Department Annapolis, Maryland	1	Commanding Officer and Director U.S. Navy Electronics Laboratory San Diego 52, California	2
ATTN: Weapons Department		ATTN: Mr. F. Hale Mr. K. V. MacKenzie	
		Director of Library U.S. Navy Postgraduate School Monterey, California	1

No. of Copies

Dr. T. G. Birdsall University of Michigan Ann Arbor, Mich.	1
R. H. Mathes U.S. Naval Research Lab. Washington, D. C.	1
Dr. W. A. Von Winkle U.S. Navy Underwater Sound Lab. New London, Conn.	1
Mr. J. Ewing Columbia University Lamont Geophysical Lab. Palisades, N. Y.	1
Mr. W. E. Hicks Pasadena Annex U.S. Navy Ordnance Test Station Pasadena, Calif.	1
Mr. S. R. Murphy Applied Physics Lab. University of Washington Seattle, Washington	1
A. J. Tickner, P-40 Naval Undersea Warfare Center Pasadena, Calif.	1
Dr. John J. Martin IDA, SED Director	1
Dr. Joshua Menkes IDA	1
Mr. A. J. Tachmindji IDA	1
Mr. Charles J. Loda IDA	1
Dr. W. D. Montgomery IDA	1
Classified Library IDA	1